



# 2023 TRX 766 i Series Specifications

	TRX 766 i Finish Cut Deck	TRX 766 i All-terrain Deck	
<b>Engine</b>	Engine	Kawasaki® FX EFI	Kawasaki® FX EFI
	Horsepower	38.5 hp	38.5 hp
	Displacement	999 cc	999 cc
	Cylinders	2	2
	Air Filter	5" Cyclonic	5" Cyclonic
	Fuel	Gasoline	Gasoline
	Fuel Capacity	14 gallons	14 gallons
	Fuel Tank	Side, Double	Side, Double
<b>Drive Line</b>	Transmission Type	Hydrostatic	Hydrostatic
	Transmission	Hydro-Gear ZT-5400 Dual Range	Hydro-Gear ZT-5400 Dual Range
	Max Forward Speed	11 mph	11 mph
	Front Tire Size	15" Flat-Free Tires	15" Flat-Free Tires
	Rear Track Size	11" x 81" Track	11" x 81" Track
<b>Dimension/ Weight</b>	Length	96"	96"
	Width (Chute Up)	67.5"	67.5"
	Height (ROPS Up)	79"	79"
	Weight	1600 lbs	1600 lbs
<b>Cutting Deck</b>	Cutting Width	66"	66"
	Deck Construction	Fabricated Steel Aero Deck	Fabricated Steel HV All-Terrain Deck
	Deck Thickness	Laminated 10 and 7 Gauge	Laminated 7 and 7 Gauge
	Deck Depth	5.5"	6"
	Cut Height (Min - Max)	2.5" - 6"	3" - 7"
	Cutting Height Steps	1/4" Increments	1/4" Increments
	Number of Blades	3	6 All-Terrain Blades
	Blade Speed	18,500 fpm	18,500 fpm
	Anti-Scalp Wheels	6 Recessed	n/a
	Deck Lifting System	Manual	Manual
	Clutch Torque	250 ft-lbs	250 ft-lbs
	Clutch Manufacturer	Warner	Warner
	<b>Warranty</b>	Homeowner/ Commercial	3 Year Unlimited Engine 2 Year Unlimited Transmission 1 Year Manufacturer
<b>Additional Features</b>		TorqFlex™ Front Suspension 12-way Adjustable Suspension Seat SmarTrac™ Pro Display Soft Start Clutch Engagement	Keyless Push-to-Start Oil Warning Light No Slip Floor Mat Turf Track



# 2023 TRX 354/561 i Series Specifications

	TRX 354	TRX 561 i	
<b>Engine</b>	Engine	Kawasaki® FT	Kawasaki® FX EFI
	Horsepower	24 hp	29.5 hp
	Displacement	726 cc	852 cc
	Cylinders	2	2
	Air Filter	Multi-Stage Canister	Multi-Stage Canister
	Fuel	Gasoline	Gasoline
	Fuel Capacity	10 gallons	14 gallons
	Fuel Tank	Side, Double	Side, Double
<b>Drive Line</b>	Transmission Type	Hydrostatic	Hydrostatic
	Transmission	Hydro-Gear ZT-3400	Hydro-Gear ZT-4400
	Max Forward Speed	8 mph	9 mph
	Front Tire Size	13" Flat-Free Tires	13" Flat-Free Tires
	Rear Track Size	11" x 71" Turf Track Standard	11" x 74" Track
<b>Dimension/ Weight</b>	Length	84.5"	93"
	Width (Chute Up)	55"	62"
	Height (ROPS Up)	76"	79"
	Weight	1220 lbs	1540 lbs
<b>Cutting Deck</b>	Cutting Width	54"	61"
	Deck Construction	Fabricated Steel Aero Deck	Fabricated Steel Aero Deck
	Deck Thickness	Laminated 10 and 10 Gauge	Laminated 10 and 7 Gauge
	Deck Depth	4.5"	5.5"
	Cut Height (Min - Max)	2.25" - 5"	2.5" - 6"
	Cutting Height Steps	1/4" Increments	1/4" Increments
	Number of Blades	3	3
	Blade Speed	18,500 fpm	18,500 fpm
	Anti-Scalp Wheels	5 Recessed	6 Recessed
	Deck Lifting System	Manual	Manual
	Clutch Torque	200 ft-lbs	250 ft-lbs
	Clutch Manufacturer	Warner	Warner
<b>Warranty</b>	Homeowner/ Commercial	3 Year Unlimited Engine 2 Year Unlimited Transmission 1 Year Manufacturer	
<b>Additional Features</b>	TorqFlex™ Front Suspension*		Oil Warning Light*
	12-way Adjustable Suspension Seat		No Slip Floor Mat
	SmarTrac™ Pro Display*		Turf Tracks*
	Soft Start Clutch Engagement*		Rear Hitch installed on TRX 354 models
	Keyless Push-to-Start*		

\*TRX 561 i models only.

Optional Independent Front Suspension available for TRX 354 models.